

COMPACT GLASS A 10

9,6 KW

COLORS_



TECHNOLOGY



OPTIONAL



Ventilazione Frontale (1 Motore) - Uscita Fumi Superiore - Uscita Fumi Posteriore - Uscita Fumi Laterale

Front Ventilation (1 Motor) - Rear Exhaust Fume Outlet - Top Exhaust Fume Outlet - Side Exhaust Fume Outlet - Ventilación Frontal (1 Motor) - Salida De Humos Trasera - Salida De Humos Superior - Salida De Humos Lateral - Ventilation Avant (1 Moteur) - Sortie De Fumée Arrière - Sortie De Fumée Supérieur - Sortie De Fumée Latéral - Front Gebläse (1 Motor) - Rauchausgang Hinten - Rauchausgang Oben - Seitlicher Rauchausgang

Potenza Globale
Global Power
Puisance globale
Potencia global
Verbrennungsleistung

Rendimento totale
Total efficiency
Puisance globale
Potencia global
Pellet Wirkungsgrad

Peso
Weight
Poids
Peso
Gewicht

Consumo min-MAX
Min-Max consumption
Consumation min-MAX
Consumo min-maxi
Min-Maxi verbrauch

Temperatura gas di scarico
Exhaust gas temperature
Température des gaz d'échappement
Temperatura de los gases de escape
Abgas Temperatur

Tiraggio richiesto in funzionamento
Draw required in operation
Dessiner nécessaire en fonctionnement
Dibujar requerido en la operación
Erforderlicher Betriebszug

Uscita fumi
Chimney Output
Sortie conduit de cheminée
Salida conducto de humos
Rauchauslass

Ingresso aria
Air inlet
Entrée d'air
Entrada aire
Lufteinlass

Serbatoio pellet
Pellet tank
Réservoir
Depósito
Tank füllungsvermögen

Assorbimento elettrico
Electrical consumption
Absorption électrique
Consumo de electricidad
Elektrischer Verbrauch

KW 9.6-3.7

% 87.5

Kg 131

Kg/H 0.8-2.3

°C 196

Pa 10

mm 80

mm 60

Kg 11

W 100



MORETTIDESIGN®